

Macrolink Fibre Channel Data Storage System

- Rugged 19 Inch 4U Rack Mounted Chassis
- 6 Hot-Swap Fibre Channel Drive Bays
- Filtered air cooled
- RFI/EMI filtering
- Module - 100,000 removal cycles
- Module - High Capacity Half-height Fibre Channel Hard Drive
- Module - protects drive during handling
- Dual Arbitrated Loop
- 1 Giga-bit interface
- User accessible FC Disk Array Address Switch



Specifications	
Features	
Input Power	114 VAC; 47-440 Hz; 350 Watt PFC
Indicators	Power
Size	19" Rack Mount, 7.00" high X 22.00" deep
Weight	52 lbs. with drives
Options	
	Fan Fail Indicator. Splash proof front door.

Environmental Capabilities		
	Operating	Non-Operating
Temperature	0° to 40° C -20° to 40° C with optional heater	-40°C to 70°C
Humidity	0% - 95% noncondensing	
Altitude	10,000 ft.	40,000 ft.
Shock	MIL-STD-810, transportation	
Vibration	MIL-STD-810, transportation	
Weather	Drip proof	
Sand/Dust	Removable air filters	
Noise	< 69 dB (A)	
Part Number	530140	

[Macrolink, Inc.](#) 1500 North Kellogg Drive Anaheim, California 92807-1902
Phone 714.777.8800 Fax 714.777.8807

Macrolink and the Macrolink logo are registered trademarks of Macrolink, Inc. Prices and specifications are subject to change without notice. Copyright 2000-2003, Macrolink, Inc. All rights reserved.

[Homepage](#) | [Contact Us](#)